



**● Intermodal Container with Tarp Top Closure System**

**Specifications**

- 25.4 cubic yard capacity
- 60,800 maximum net weight capacity (actual weight will vary per transportation method)
- 6,400 lbs. tare weight
- Outside dimension 238 1/2" L x 96" W x 78" H
- Inside dimension 230" L x 85" W x 61" H
- Tarp opening same as inside dimension

**Equipment Features**

- MHFU Reporting Marks
- Containers are certified for international transport by container ship, as well as barge, rail flatcar, flatbed truck or roll-off truck
- MHF-LS containers are uniform in construction and operation; the containers can be double-stacked on our ABC railcars
- Container can be lifted by crane, sidelifter, forklift, roll-off truck or container handler
- Rear door can be side or top-hinged
- Watertight design and construction
- Full top access with tarp removed

**Equipment Advantages**

- All containers are equipped with bottom flapper secondary tailgate closure system, the most secure closure for rail transport in the industry
- Ideal for bulk solids such as soils, sludges, rubble, metals and construction debris
- Watertight rear door gasket system
- Lease or purchase options

**Certifications**

Container is manufactured under a Nuclear Quality Assurance (NQA-1) Program, which provides assurance of conformity to the following certifications:

Containers meet DOT package specifications under 49 CFR 173.240. Sift-proof and 49 CFR 173.427 "Strong-Tight" and is ABS/AAR approved.

**Hydrostatic & Water Penetration Testing**

- Internally water tested: The containers are completely filled with water to determine that all welds are watertight. The test is documented with a water test certificate.
- External spray test: All containers with lids must pass an external "weather tightness" test in accordance with procedures. The test is documented with an external spray test certificate.

**Security & Safety**

Security seals are available for purchase in various styles that deter unauthorized access. Many safety features are engineered into our equipment, containers and packages and are referenced in the specifications, equipment features and advantages.