



● Cargo Container 20' DOT IP-1

Specifications

- 60,000 lbs. maximum net weight capacity (actual weight will vary per transportation method)
- Outside dimension 240" L x 96" W x 102" H
- 1,162 cubic foot internal volume
- 7,200 lbs. tare weight

Equipment Features

- MHFU Reporting Marks
- Maintained in good condition; high corrosion resistant coatings have been applied
- Modified door seals to meet 49 CFR 193.410
- ABS/ISO certified lifting mechanisms
- Open top or end-loading capabilities
- Gasketed watertight design and construction with steel floor
- Fork pockets reinforced to meet 49 CFR 173.410

Equipment Advantages

- Stackable to five high
- Liners/shielding inserts available
- Higher tops can be added to accommodate 110" heights
- Custom modifications available to aid in the transport of any type of package or cargo
- Lease or purchase options

Certifications

Container is manufactured under a Nuclear Quality Assurance (NQA-1) Program, which provides assurance of conformity to the following certifications:

ABS/ISO 49 CFR 173.427
 49 CFR 173.410 (IP-1)
 ISO 1496-1
 CSC Safety Approval as manufactured

Light & Hydrostatic Water Testing

- Light test: All containers with lids must pass an internal light test. Under procedure, an inspector is placed into a closed container to verify that container is light tight. The test is documented with a light test certificate.
- External spray test: All containers with lids must pass an external "weather tightness" test in accordance with procedures. The test is documented with an external spray test certificate.

Security & Safety

Security seals are available for purchase in various styles that deter unauthorized access. Many safety features are engineered into our equipment, containers and packages and are referenced in the specifications, equipment features and advantages.